



VERSION 20.0

WRAPTOR® TAPE

HOUSE WRAP TAPE

WEATHER BARRIERS

DIVISION
072500

PRODUCT NAME

WrapTOR® Tape House Wrap Tape

MANUFACTURER

ISI BUILDING PRODUCTS
401 Truck Haven Road
East Peoria, IL 61611
866.698.6562 / www.isibp.com

PRODUCT DESCRIPTION

BASIC USE

WrapTOR Tape is used to seal vertical and horizontal seams in WrapTOR or WrapTOR HP during house wrap installation. WrapTOR Tape provides a continuous barrier against water and air infiltration.

COMPOSITION & MATERIALS

WrapTOR Tape is comprised of translucent poly film with an aggressive adhesive.

SIZE

Standard Sizes: 2" x 55 yd.

WEIGHT

Approximately 1 lb. per roll.

INSTALLATION

PLACEMENT

Align bottom edge of house wrap to the bottom portion of the wall and unroll against the wall sheathing.

Fasten with plastic cap nails, staples or large head nails. When installing over foam sheathing, fasteners should penetrate structural framing at least half inch.

Overlap all vertical seams a minimum of six inches. Horizontal seams should be overlapped a minimum of eight inches.

All seams, tears and protrusions of house wrap should be taped with WrapTOR Tape.

For window and door details refer to the WrapTOR Installation Guide available from the manufacturer.

PROTECTION

WrapTOR should be covered with the exterior cladding as soon as it is practical (maximum one hundred and eighty days).

When using WrapTOR behind stucco, a lathe system should be employed. In moist or humid areas, check local codes for proper moisture control practices. Some areas may require two layers of house wrap and/or an additional drainage plane behind stucco finishes.

Back-priming of wood or other porous siding is recommended before installing over house wrap.

These are general installation instructions. Instructions on architectural or structural drawings should be reviewed and followed. Detailed installation instructions can be obtained by calling the manufacturer at 866.698.6562 or visiting www.isibp.com.

WARRANTY

Warranty information can be obtained by calling the manufacturer at 866.698.6562 or visiting www.isibp.com.

MAINTENANCE

Requires no maintenance once installed.

TECHNICAL SERVICES

Technical information and detailed test results can be obtained by calling the manufacturer at 866.698.6562.

FILING SYSTEMS

Additional information can be obtained by calling the manufacturer at 866.698.6562 or visiting www.isibp.com.

DISCLAIMER: TO THE BEST OF OUR KNOWLEDGE, THE SPECIFICATION CHART LISTS TYPICAL PROPERTY VALUES AND ARE INTENDED AS GUIDES ONLY, NOT AS SPECIFICATION LIMITS. ISI BUILDING PRODUCTS MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, NO GUARANTEE OF SATISFACTORY RESULTS FROM RELIANCE UPON CONTAINED INFORMATION OR RECOMMENDATIONS AND DISCLAIMS ALL LIABILITY FOR RESULTING LOSS OR DAMAGE.



AN AFFILIATE OF MEYER ENTERPRISES, LLC
401 TRUCK HAVEN ROAD, EAST PEORIA, IL 61611
PHONE: 309.698.0062 / FAX: 309.698.0065